



Drehmoment / Torque
 Zahnkranz / Spider 98 Sh A
 Tkn = 17 Nm
 Tkmax = 34 Nm
 Teil 5: Schraubenanzugsmoment: 10.5 Nm
 Part 5: Screw Tightening Torque
 Teil 4: Schraubenanzugsmoment: 10.5 Nm
 Part 4: Screw Tightening Torque

We reserve the right to make dimensional and design changes.

Order details			
Pos.	No	Description	Part Number
5	1	Cap screw M6X16 DIN912-12.9	004065060161
4	1	Cap screw M6X16 DIN912-12.9	004065060161
3	1	ROTEX GS 19 AL-H clamp hub 2.5 Ø12H7 w/o key	550197151250
2	1	ROTEX GS 19 spider 98 Sh-A-GS red	550191000002
1	1	ROTEX GS 19 AL-H clamp hub 2.5 Ø8H7 w/o key	550197150850

		Oberflächengüte nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2		Schutzvermerk nach DIN 34 beachten Note protection mark acc. to DIN 34				
		Allgemeintoleranz nach DIN ISO 2768-mH General tolerances acc. to DIN ISO 2768-mH		Masstab Scale	1: 0.66	Format DIN Size	A3	
		ROTEX® GS 19 Standard			 KTR Kupplungstechnik GmbH D-48407 Rheine			
	gezeichnet drawn	Werkstoff Material		Teilnummer Part Number	Kz	Lfd.-Nr. Current number	Index Change	
Datum date	06.12.2013	DIN						
Name name		Gewicht Weight						



ROTEX